



## Möbelöl

The wood treatment for durable interior surfaces. A silky glossy, hard-wearing, dirt and water repellent surface finish is achieved. Quick and easy application. The natural oils penetrate deep into the wood. They keep it healthy and elastic and do not let it dry out. Good refresher for already oiled wood. No sanding required for after-treatment.



## Product description

### Application area

A high quality oil resin treatment for all oiled furniture indoors as well as covered outdoor areas, such as garden furniture. Very suitable for tropical woods, such as Bangkirai. High-quality vegetable oils impregnate new wood and refresh old.

## Processing

### Processing

Stir / shake container well before use. The optimum processing temperature is above 15°C. The untreated wood substrate must be dry, clean and free of resin and dust. Carry out fine final sanding with grit 180 - 240 depending on the type of wood. Apply evenly with a brush and spread thoroughly. After a short exposure time, rub excess oil lightly with a clean and lint-free cloth and remove excess material. Repeat this treatment 2 - 3 times.

### Usage

The application quantity must be determined by trial application at the beginning of processing. Empirical values depending on absorbency and final sanding of the wood: 50 - 70 ml/m<sup>2</sup>.

### Drying time

At 20°C and medium humidity dry after 6 hours, recoatable after 16 - 24 hours.

### Cleaning the tools

With Le Tonkinois Verdünnung.

## Substrates and their pretreatment

---

<b>Underground</b>	Dry (wood moisture max. 14%), solid, absorbent, clean, free of resin and dust.
--------------------	--

## Product information

---

<b>Ingredients</b>	Boiling of linseed oil, derizole oil, tung oil and rosin; lacquer linseed oil; derizole oil; leucophyllites; zinc oxide; diatomaceous earth; wax; bentonites; no cobalt or its polymers.
--------------------	--

---

<b>VOC Safety Notice</b>	The VOC content of this product is max. 1 g/l. EU limit 400 g/l.
--------------------------	--

---

<b>Storage</b>	Store in a cool place.
----------------	------------------------

---

<b>Shelf life</b>	Shelf life unopened at least 5 years.
-------------------	---------------------------------------

---

<b>Disposal</b>	In accordance with local, official regulations. Dried up product residues can be disposed of with household waste. Waste code: 08 01 11
-----------------	---

---

<b>Safety instructions</b>	<p>For safety-relevant information, please refer to the corresponding safety data sheet.</p> <p>Natural paints have a characteristic odor due to the vegetable oils used. Ensure good ventilation during processing. Drying oils can ignite spontaneously. Therefore, do not crumple up rags contaminated with this product, but let them dry spread out or soak them in water before disposing of them.</p>
----------------------------	--

To achieve optimum results, please observe the technical data sheets of all products used.  
The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.