



Hartöl

The wood treatment for interior surfaces subject to wear. A silky glossy, hard-wearing, dirt- and water-repellent surface is achieved. Resistant to common household liquids.



Product description

Application area

For the treatment of untreated or oiled surfaces of all types of wood and wood-based materials in interior areas. For floorboards, wood-based panels, OSB panels or wooden parquet as well as for unglazed terracotta tiles.

Processing

Processing

Stir / shake container well before use. Apply Le Tonkinois Hard Oil thinly and evenly with a flat brush or short pile roller. Allow to dry and if necessary, if a 2nd application is required, intermediate sanding is possible. Apply the hard oil sparingly a second time within approx. 12 - 16 hours.

During application and drying of the products, ensure optimum fresh air circulation! Otherwise odor nuisance possible!

Usage

1 coat 18 m²/l 2 coats 14 m²/l.

Drying time

The drying time is approx. 16 - 24 hours (20 - 23°C / 50 - 55% relative humidity). Complete drying and full loading capacity after 7 - 10 days.

Cleaning the tools

With Le Tonkinois Verdünnung.

Substrates and their pretreatment

Underground	The substrate must be dry (wood moisture max. 14%), clean and dust-free. The application temperature should preferably not be below 12°C. Lower temperatures delay the drying behavior. Final sanding of the surfaces with at least 120 grit or grid.
--------------------	---

Product information

Ingredients	Aromatics free aliphatic hydrocarbons, decoction of derizole oil, rosin and tung oil, bentonite, talc, wax, zinc oxide, lead and cobalt free drying agents.
--------------------	---

VOC Safety Notice	The VOC content of this product is max. 490 g/l. The EU limit is max. 700 g/l (category f from 2010).
--------------------------	--

Storage	Store in a cool and dry place. Close container tightly.
----------------	---

Shelf life	Closed about 5 years.
-------------------	-----------------------

Disposal	In accordance with local, official regulations. Dried product residues can be disposed of with household waste. Waste code EAK 08 01 11
-----------------	---

Safety instructions	For safety-relevant information, please refer to the corresponding safety data sheet. Natural paints have a characteristic odor due to the vegetable oils used. Ensure good ventilation during processing. Drying oils can ignite spontaneously. Therefore, do not crumple up rags contaminated with this product, but let them dry spread out or soak them in water before disposing of them.
----------------------------	---

To achieve optimum results, please observe the technical data sheets of all products used.
The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.