

Hartwachs

Colorless wax preparation.



Product description

Application area	For the care and finishing of untreated or primed wood surfaces in the interior such
	as furniture, doors, etc. Not suitable for floors!

Processing

Processing	Rub in thinly with cloth or brush. If necessary, apply a second coat after intermediate drying. Do not apply below 16°C. To obtain a silky glossy surface, it can be repolished with a polishing brush or a lint-free cloth under light pressure. Do not treat with aggressive cleaning agents.
Usage	25 - 50 m²/l
Drying time	Can be polished at 20°C after approx. 10 - 20 min. Softening after a few hours.
Cleaning the tools	With Le Tonkinois Verdünnung.

Substrates and their pretreatment

Underground	Dry, free of dust and grease. Rub down resin-rich and tropical woods with
	Le Tonkinois Thinner beforehand. Allow to dry well before further treatment.

Stand: 30.07.2024 www.le-tonkinois.com Seite 1 von 2

TECHNICAL DATA SHEET

Hartwachs



Product information

Ingredients	Aromatics free aliphatic hydrocarbons, beeswax, carnauba wax
VOC Safety Notice	The VOC content of this product is max. 650 g/l.
Storage	Stable for at least 4 years when originally sealed. Store in a cool, dry and closed place.
Disposal	In accordance with local, official regulations. Dried up product residues can be disposed of with household waste. Waste code: 08 01 11
Safety instructions	When grinding, do not inhale dusts - wear protective mask.
	For safety-relevant information, please refer to the corresponding safety data sheet.

To achieve optimum results, please observe the technical data sheets of all products used.

The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.