



Terrassenöl

Quick and easy application, for the treatment of wooden decking. The natural oils penetrate deep into the wood. They keep it healthy, elastic and do not let it dry out. Good refresher for already oiled wood. No sanding required for renovation painting.



Product description

Application area

For all outdoor woods, such as wooden terraces, fences, pergolas, children's playground equipment and garden furniture, etc. Very suitable for tropical woods, such as z. e.g. Bangkirai. High-quality vegetable oils impregnate new wood and freshen up old.

Processing

Processing

Stir well before use. The substrate must be dry, solid, clean, free from grease free of grease and dust, and absorbent. Pre-treat grayed, dirty wood with Le Tonkinois Entgrauer and wash off, sand down if necessary.

Do not apply at temperatures below 10°C. Apply with a brush in a saturated and even coat. After application, remove oil that has not been absorbed after approx. after approx. 5 minutes with the brush. Remove excess oil with a with a lint-free cloth. Allow to dry thoroughly.

Usage

Approx. 60 - 80 ml/m², may vary depending on the absorbency of the substrate.

Drying time

At 20°C and medium humidity dry after 6 - 8 hours, recoatable after 16 - 24 hours recoatable.

Cleaning the tools

With Le Tonkinois Verdünnung.

TECHNICAL DATA SHEET

Terrassenöl



Substrates and their pretreatment

Underground	Dry, solid, clean, absorbent, free of grease and dust.
--------------------	--

Product information

Ingredients	Isoaliphates, natural vegetable oils, resins, drying agents, 3-Iodo-2-propynyl butyl carbamate.
--------------------	---

VOC Safety Notice	VOC content of this product is max. 450 g/l. EU limit max. 700 g/l.
--------------------------	---

Storage	Store in a cool, dry and closed place.
----------------	--

Shelf life	Original sealed stable for at least 5 years.
-------------------	--

Disposal	In accordance with local, official regulations. Dried up product residues can be disposed of with household waste. Waste code: 08 01 11
-----------------	---

Safety instructions	<p>For safety-relevant information, please refer to the corresponding safety data sheet.</p> <p>Natural paints have a characteristic odor due to the vegetable oils used. Ensure good ventilation during processing. Drying oils can ignite spontaneously. Therefore, do not crumple up rags contaminated with this product, but let them dry spread out or soak them in water before disposing of them.</p>
----------------------------	--

To achieve optimum results, please observe the technical data sheets of all products used.
The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.