



Vernis

The Le Tonkinois Vernis formula is based on a centuries-old tradition of protection for wood and metals. Le Tonkinois, a product of the highest purity, is made, for more than 100 years according to proven artisan methods exclusively from the best linseed and a part of pure China wood oil is added, is an oil that is not surpassed by any chemical product.



Product description

Application area

On wood and degreased metals, Le Tonkinois Vernis forms a durable protection and has a high UV resistance. Highly effective even for many years in extreme weather conditions. Le Tonkinois Vernis is the perfect protection for any exterior or interior wood, preserving the natural, warm character of the wood for almost unlimited time, even under extreme climatic conditions. Wind and weather can destroy the natural beauty of wood. Natural surfaces impress with their beautiful wood grain, which is further fueled by Le Tonkinois.

Processing

Processing

Adjusted ready for use. Stir well before use. Do not dilute. Apply with brush, flat brush. For spraying, dilute max. 5% - 10% with Le Tonkinois Verdünner. For sanding work such as intermediate sanding, max. 180 grit is sufficient. Do not apply at temperatures below 12°C.

The coats should always be applied thinly by rolling or brushing and only one coat should be applied daily. Particularly suitable for the preservation of historical monuments.

Usage

30 - 50 ml/m² or 20 m²/l, per coat depending on the surface condition and absorbency of the substrate, based on smooth and planed/sanded surfaces. Absorbent substrates may result in higher consumption values for the first coat.

TECHNICAL DATA SHEET

Vernis

Drying time

At 20°C and medium humidity after 6 - 8 hours, if possible wait 24 hours for recoating. Low temperatures, high humidity and low air exchange delay drying and promote odor formation. Ensure good ventilation during application. Load surfaces only carefully at first. Surfaces can be walked on after 3 days with 2 - 3 coats.

Substrates and their pretreatment

Underground

Untreated wood, wood-based materials, also on cork to a limited extent. Rough wood substrates must be carefully sanded. The wood surface must be free of dust and grease, clean, dry and frost-free (max. 15% wood moisture).

Product information

Ingredients

Linseed oil, tung oil, natural resins, isosalphates

VOC Safety Notice

The VOC content of this product is max. 400g/l.

Storage

Store well closed, dry, cool, but frost-free.

Shelf life

Shelf life min. 5 years in unopened original container.

Disposal

Dispose of product residues and packaging in accordance with local regulations. Only recycle empty cans.

Safety instructions

For safety-relevant information, please refer to the corresponding safety data sheet.

To achieve optimum results, please observe the technical data sheets of all products used.

The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.