



Arbeitsplattenöl

Solvent-free, refines the wood permanently and guarantees a resistant surface. Impregnating, water-repellent, open-pored, vapor-permeable.



Product description

Application area For impregnation of kitchen countertops, furniture surfaces and other wooden surfaces.

Processing

Processing Apply by spraying or rolling, brush, sponge or lint-free cloth and spread thoroughly. Allow to react for at least 20 minutes. Then absorb excess oil and polish out evenly with white pad. Depending on the desired surface appearance, a second coat can be applied.

Usage Application quantity must be determined in advance by trial application. Empirical values depending on absorbency and final sanding of the wood:
1st application 25 - 35 g/m²
2nd application 5 - 10 g/m²

Drying time The drying time depends on the environment. The drying time at 20 - 23°C is 6 - 12 hours, depending on the amount of oil applied.
This system requires sufficient quantities of atmospheric oxygen for drying. Therefore, ensure good ventilation to avoid odor formation.

Substrates and their pretreatment

Underground	The substrate must be dry (wood moisture max. 14%), solid, absorbent, clean, and free of resin and dust. Good final sanding with grit 180 - 240 depending on the type of wood. Stir carefully before use.
--------------------	---

Product information

Ingredients	Decoction of tung oil, linseed oil, stand oil and rosin, leucophyllite, soy stand oil, Zinc oxide. Free from dry materials such as cobalt and its polymers.
VOC Safety Notice	The VOC content of this product is max. 1 g/l. The EU limit is max. 700 g/l (category f from 2010).
Storage	Store in a cool and dry place. Close opened containers tightly, decant leftovers into smaller containers.
Shelf life	Shelf life unopened at least 5 years.
Disposal	In accordance with local, official regulations. Dried product residues can be disposed of with household waste. Waste code: EWC 08 01 12
Safety instructions	For safety-relevant information, please refer to the corresponding safety data sheet. Natural paints have a characteristic odor due to the vegetable oils used. Ensure good ventilation during processing. Drying oils can ignite spontaneously. Therefore, do not crumple up rags contaminated with this product, but let them dry spread out or soak them in water before disposing of them.

To achieve optimum results, please observe the technical data sheets of all products used.
The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.